

## **HR-System according to IEC 61243-5** **IVI 3000/3 PART OF SYSTEM 3000**

Capacitive coupled 3-phase voltage present indicator



### **IVI 3000/3 – Designed according to IEC 61243-5.**

- IVI 3000/3 voltage present indicator for HR-system (90V)
- No external matching capacitor needed. (Integrated part of IVI 3000/1)
- Long life low energy LED indicator for voltage present / voltage absent.
- Integrated over voltage and transient voltage protection.

### **TECHNICAL DATA.**

- Frequency 50 – 60HZ.
- Degree of environmental protection: IP54 (Epoxy filled housing.)
- Ground wire 0,5m 1,5mm<sup>2</sup> with M8 ring cable shoe.
- Connection L1, L2 and L3: Faston 6,3 x 0,8mm. Other termination and cable details upon request.
- 3 of 4 mm banana socket (Safety type). Suitable for safety plug on Phase Comparator type FF2.0 / FF3.0
- Temperature range: -25<sup>0</sup>C to +65 <sup>0</sup>C.

### **SPECIAL FACILITIES.**

- IVI 3000/3 needs no external auxiliary voltage source.

**Tel.: 00 47 911 76 949. Fax.: 00 47 3333 8220 Tel.: 00 47 3333 8038**

[www.hegna-electronics.com](http://www.hegna-electronics.com)

Mail: [hegna@hegna-electronics.com](mailto:hegna@hegna-electronics.com)